I-81/NYS 17 Prospect Mountain Interchange Improvements Project

Broome County, NY

81


Transportation Research Board ADC40 *Transportation-Related Noise & Vibration*2017 Summer Meeting

Joe Van Kerkhove, PE Ken Avery, PE










Project Location



Selected Alternative



Interchange Timeline



1960's
Original
Construction

1999 NYS Rte 17 / I-81 Corridor Noise Study

2008 Design Approval 2015 2016

Phase 1 Phase 2

Construction Construction

Completed Commences



















1995 Interchange Study 2007 Project Noise Study

2013 - 2015 Phase 2 Design & Re-Evaluation Noise Study

1999 Corridor Noise Study





2007 Original Project Noise Study

TRANSPORTATION

NOISE REPORT

NYS ROUTE 17/INTERSTATE 81 INTERCHANGE SH 63-24, SH 64-1, SH 64-4, SH 64-5, SH 68-8 PIN 9500.61 CITY OF BINGHAMTON TOWN OF DICKINSON BROOME COUNTY


> Prepared By: McFarland-Johnson, Inc. 49 Court St., P.O. Box 1980 Binghamton, NY 13902

> > May 2007



NEW YORK STATE
DEPARTMENT OF TRANSPORTATION
ASTRID C. GLYNN, Commissioner
ELIOT L. SPITZER, Governor

PROJECT REPORT



2013 – 2014 Additional Noise Analyses


Western Limit Extends to NYS 17 at Airport Road Eastern Limit Extends to I-81/NYS 17 at I-86 Approx. 7.5 miles





Phase 2 – Noise Analysis & Design

- NYSDOT added adjacent Noise study areas from the 1999 Corridor Study – Bergmann scoped to complete noise analyses of these areas
- Bergmann also scoped with Final design of 6,500 ft of Noise Barriers that were already recommended for construction in the 2007 Noise Study
- As a result of Bergmann 2013 Noise Analyses, additional noise barriers are recommended for construction
- NYSDOT DETERMINES THAT ADDITIONAL NOISE REVIEW MUST FALL UNDER A RE-EVAUATION PROCESS




Phase 2 Project Elements (Re-Evaluation Items)

NEPA Re-Evaluation Statement!

- A. Non-Standard Highway Features
- B. Milling and Resurfacing Roadways
- C. Modifications / Reconstruction of Highway X-Culvert
- D. Additional Drainage Inlets
- E. Extension of Acceleration Lane
- F. Addition of Temporary Bridge
- G. Addition of Concrete Median
- H. Extension of Eastern & Western Limits for the Purpose of Noise Analyses to coincide with limits of Enhanced ITS work

Phase 2 Further Extends Noise Project Area Limits



Phase 2 Project Elements (NYSDOT Noise Policy)


- 2007 Study was performed using Previous Policy
- Updated NYSDOT Policy in 2011 was in place during 2013 & 2014 Studies
- Major Change in Policy was the reasonableness Cost Index for abatement measures
- Previous Policy A maximum \$50,000 wall cost per benefitted receptor applied
 - Current Policy A maximum of 2000 sq-ft of wall per benefited receptor applies
- Decision made to use Previous Policy since noise barriers were found feasible & reasonable to build in the original study area of the Project

Phase 2 Project Elements (Additional Noise Analysis Locations)

- NYSDOT requested that Bergmann perform additional noise measurements and analyze locations not included in the studies - Residential property owners claimed that they were not considered in any of the Project Noise Studies
- Seemed to be problematic at first because the noise studies had already identified impacts and recommended noise barriers for construction
- Fortunately, we able to resolve these issues

Phase 2 Project Elements (Additional Noise Analysis Locations)

Additional Site #1



Residential Property fell inside a "gap" in the defined noise study area from the original 2007 study, and the study area scoped by NYSDOT for the 2013 study; and was then overlooked when defining study areas in 2014

Phase 2 Project Elements (Additional Noise Analysis – Site #1)

- Measurements were taken, and analysis was performed using the TNM model already created for the 2013 Study.
- NO Traffic Noise Impacts identified at this residential property
- An updated barrier analysis was performed by extending the adjacent recommended wall (NB-1)
- Wall height in excess of 30 feet was required to achieve a 5 dBA reduction at the property
- Additional wall area would make it fail reasonableness criteria – NB-1 remained as identified in 2013 Study

Phase 2 Project Elements (Additional Noise Analysis Locations)

Additional Site #2




Residential Property was not within any of the noise study areas from the 1999 study, and during the reevaluation review this neighborhood was left out of the noise study due to its distance from the highway.

Phase 2 Project Elements (Additional Noise Analysis – Site #2)

- Measurements were taken, and analysis was performed using the TNM model already created for the 2013 Study.
- NO Traffic Noise Impacts identified at this residential property
- An updated barrier analysis was performed by extending the adjacent recommended wall (NB-13)
- Distance between highway and nearest property is (~400 ft), and it was not possible to achieve a 5 dBA reduction at the property
- NB-13 remained as identified in 2013 Study







Phase 2 Noise Barriers


Match Phase 1 Noise Barriers



Most Noise Barriers being Constructed are standard ground-mounted but several other foundation types / mounting systems were used

Western Limit Noise Barriers

West of Phase 1



North Side (NB-1): 775 m (+/-) South Side (NB-2): 375 m (+/-)

Sub-Total (This Graphic): 1,150 m (+/-)


Soldier Pile Wall


Sowden Street




Soldier Pile Wall

Sowden Street








Soldier Pile Wall


Sowden Street



NY 17 WB Over Glenwood Ave




NY 17 WB Over Glenwood Ave



Phase 2 Noise Barriers

Interchange 3 and 4




North side (NB-3, 5, 6 & 8): 125 m, 340 m, 240 m & 250 m (+/-) South side (NB-4, 7, & 9): 270 m, 245 m and 530 m (+/-)

Sub-Total (This Graphic): 2,000 meters (+/-)

Fill-Type Retaining Wall


NBON



Noise Barrier mounted on Moment Slabs on top of Retaining Wall

Fill-Type Retaining Wall

NBON



Noise Barrier (Transparent-Bridge Mount)

ACRYLITE® Soundstop
TL4 System



Meets NCHRP 350, Test Level 4 crash test and 2012 AASHTO LRFD

Eastern Limit Noise Barriers

East of Interchange 3 and Bigelow Street






North Side (NB-11 & 14): 305 m & 320 m (+/-) South Side (NB-12 & 13): 405 m & 370 m (+/-)

Sub-Total (This Graphic): 1,400 meters (+/-)

Phase 2 Total: 4,550 m (+/-) Approx. 3 miles


Noise Barrier (Ground Mount)

Phase 1 Design



Noise Barrier (Ground Mount)

Phase 2 Design



- 2012 LRFD Noise Barriers must resist vehicular collision forces unless it has been crash-tested or meets setback requirements.
- Requirements adopted by NYSDOT in April 2014

Phase 2 Cost

Total Project BID = \$150 Million

Noise Barrier Items BID = \$15 Million

Noise Barriers 10% of Overall Project

TNM Training Comes to Life



